

# ALTO

## INTERNAL SOUNDER



### SOSP/ALTO/WH/G Combined Internal Sounder and Extension Speaker

- Low Profile Design
- 110dB(A) sound output
- Connect either as a sounder or speaker
- Selectable alternating or continuous tone
- Low current consumption
- Tamper protected lid and mounting
- High Impedance allowing multiple speakers to be used



### SP/ALTO/WH Extension Speaker

- Low Profile Design
- Tamper protected lid and mounting
- Dynamic piezo technology
- High Impedance allowing multiple speakers to be used
- Does not require any 12volt power supply

### SO/ALTO/WH/G Internal Sounder

- Low Profile Design
- 110dB(A) sound output
- Selectable alternating or continuous tone
- Low current consumption
- Tamper protected lid and mounting
- *3rd Party Tested*

## TECHNICAL SPECIFICATIONS

### Internal Sounder

<b>Nominal Power Supply:</b>	6-14V DC
<b>Current Draw:</b>	103mA MAX.
<b>Sound Output:</b>	110dB(A)
<b>Colour:</b>	White
<b>Tamper:</b>	Cover & Wall
<b>Material:</b>	ABS
<b>Dimensions:</b>	115 x 115 x 32mm
<b>Product Code:</b>	SO/ALTO/WH/G
<b>EN Grade:</b>	3
<b>Environmental Class:</b>	II

### Extension Speaker

<b>Nominal Impedance:</b>	Better than 16 ohms
<b>Speaker Type:</b>	Tone (Piezo)
<b>Sound Output Level:</b>	>100 dB(A) @ 1 metre
<b>Temperature Range:</b>	-15°C to +40°C
<b>Tamper:</b>	Cover & Wall
<b>Material:</b>	ABS
<b>Dimensions:</b>	115 x 115 x 32mm
<b>Product Code:</b>	SP/ALTO/WH

### Combined Internal Sounder and Extension Speaker

<b>Internal Sounder:</b>	As specifications above
<b>Extension Speaker:</b>	As specifications above
<b>Product Code:</b>	SOSP/ALTO/WH/G



Contact us:

**Phone:**

Tel: +44(0)151 6061000  
Fax: +44(0)151 6061122

**Online:**

Web: [www.cqr.co.uk](http://www.cqr.co.uk)  
Email: [info@cqr.co.uk](mailto:info@cqr.co.uk)



**Address:** CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.

