Declaration of Performance No. 0359-CPR-0171 REV 01

Declaration of Performance according to the Construction Products Regulation EU No. 305/2011

B (4.) 70
Brand(s): Ziton
Each individual product is identified with a label containing a unique serial number.
Fire detection and fire alarm systems – Input/output devices EN54-18
Fire detection and fire alarm systems – Components using radio links EN54-25
EMS Security Group Limited
Technology House, Sea Street, Herne Bay, Kent, CT6 8JZ
EMS Security Group Limited
Technology House, Sea Street, Herne Bay, Kent, CT6 8JZ.
System 1
Intertek – 0359; performed type testing and the initial inspection of the manufacturing plant and of the factory production control with continuous surveillance assessment and approval of the factory production control under system 1 and issued an EC certificate of conformity.
0359-CPR-0171
Not applicable, see point 7

^{9.} Declared performance: All requirements including all Essential Characteristics and the corresponding performances for the intended use or uses indicated in point 3 above have been determined as described in the harmonised technical specifications: EN54-18:2005 and EN 54-25: 2008 mentioned in the table(s) below.

Fire detection and fire alarm systems – Input/output devices ${\tt EN54-18}$

5.2 (see note 1) 5.1.4 5.1.4 5.3, 5.4 5.8 to 5.11
5.1.4 5.3, 5.4 5.8 to 5.11
5.3, 5.4 5.8 to 5.11
5.8 to 5.11
0.000
5.5, 5.6
5.7
5.2, 5.12

Fire detection and fire alarm systems - Components using radio links EN54-25

F		D ' I I I I I I I
Essential characteristics	Performance	Requirement clauses in this European standard
Performance parameters under fire	PASS	4.1, 4.2.2, 5.2, 8.3.7 (see note a)
conditions		
Response delay (response time to fire)	PASS	8.2.3, 8.2.6 (see note a)
Operational reliability	PASS	4.2.1, 4.2.3 to 4.2.7, 5.3, 5.4, 6, 7, 8.2.2, 8.2.4, 8.2.5, 8.2.7, 8.2.8 ^b , 8.2.9, 8.3.1, 8.3.2, 8.3.3, 8.3.5, 8.3.6
Durability of operational reliability,	PASS	8.3.9°, 8.3.10°, 8.3.11
Temperature resistance		
Durability of operational reliability,	PASS	8.3.16 ^c , 8.3.17 to 8.3.19
Vibration resistance		
Durability of operational reliability,	PASS	8.3.12 ^d , 8.3.13 ^e , 8.3.14
Humidity resistance		
Durability of operational reliability,	PASS	8.3.15°
Corrosion resistance		
Durability of operational reliability,	PASS	8.3.20
Electrical stability		

- a The products covered by this standard are assumed to enter the alarm condition, in an event of fire, before the fire becomes so large as to affect their functioning. There is no requirement to function when exposed to direct attack from fire.
- b Only applicable to components required to indicate loss of communication or to transmit this information to the CIE.
- c Not applicable for CIE.
- d Not applicable for CIE and smoke detectors.
- e Only applicable for CIE and smoke detectors.
- 10. The performance of the product identified in items 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed by: Terry Kennedy

Technical Compliance Manager

Signed by: Dr. Robert Dudley

Product and Compliance Director

Location: EMS Security Group Limited,

Technology House, Sea Street, Herne Bay, Kent, CT6 8JZ, U.K. Date: 1st July 2013

Regulation (EU) No. 305/2011 CPR Supplementary CE marking information		
(€		
Identification of the Certification Body: 0359		
Manufacturer: EMS Security Group Limited, Technology House, Sea Street, Herne Bay, Kent, CT6 8JZ, U.K.		
Last two digits of year CE mark was first placed: 12		
Declaration of Performance (DoP) Number: 0359-CPR-0171 REV 01		
EN54-18:2005 and EN 54-25:2008		
Unique identification of product type: See the product label for the product documentation part number and revision.		
Intended use: See DoP point 3.		
Essential characteristics: See DoP point 9.		